

BUILT IN

INSERT

14 & 18 KW SINGLE SIDED



A NEW GENERATION IN HEATING



14 KW INSERT C/W BLACK BORDER GLASS

These units are higher heat out-put additions to our insert range. Like our smaller inserts they are designed to be built into a brick structure/chimney.

NEW FEATURES

1 TOUCH AIR CONTROL

Traditionally wood stoves have two air control levers - one to control the primary air brought into the base of the fire - and one to control air brought into the top of the fire. This is to improve combustion efficiency, lower emissions into the atmosphere, and keep the door/glass clean and cool. There is some thought involved in how to adjust these controls correctly for best effect combustion.

INSERT	a	b	c	d	e	f	g	h	i	j
14 Kw STD	860	620	418	803	99	319	28	30	27	471
14 Kw BBG	860	620	428	803	99	329	28	30	27	471
18 Kw STD	1100	565	500	1030	148	352	35	36	5	N/A
18 Kw BBG	1100	565	500	1030	138	362	35	36	5	N/A

Our 14 & 18 Kw single sided stoves utilise our **1 Touch Air Control**. This single air control is located at the bottom of the door, where it is much cooler to the touch. It easily adjusts air flow in the correct proportions to the top, rear and base of the stove, to maximise efficiency and ensure clean burning - making these units much simpler to use than many other wood stoves.

CHOICE OF GLASS





Our 14 & 18 Kw single sided stoves come in a choice of a Clear Glass at the rear of the door or a Black Border Glass located at the front of the door, for a more sophisticated look.

AIR INLET RESTRICTOR

Easily set to prevent over burning when installed with a long chimney or in high wind areas.

HEATING CAPACITY

14 Kw ► 560 m³ | 18 Kw ► 720 m³



14 KW | INSERT | 1 TOUCH AIR CONTROL | AIR INLET RESTRICTOR | 150 MM DIAMETER FLUE | TOP OR REAR EXIT

18 KW | INSERT | 1 TOUCH AIR CONTROL | AIR INLET RESTRICTOR | 75 MM DIAMETER FLUE | TOP EXIT ONLY